



(19)

(11) Publication number: **2002**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **2000252149**(51) Intl. Cl.: **C23C 4/16 B05B 7/16 B05D
7/22 C23C 4/06 F16L 58/08**(22) Application date: **23.08.00**

(30) Priority: (43) Date of application publication: 28.02.02 (84) Designated contracting states:	(71) Applicant: SHINWA KOGYO KK UMAGOME MASAKATSUGU (72) Inventor: UMAGOME MASAKATSUGU NISHIWAKI HIDEO (74) Representative:
--	---

(54) METHOD FOR FORMING SPRAYED COATING ON INNER SURFACE OF METAL TUBE, AND THERMAL SPRAYING GUN AND THERMAL SPRAYING APPARATUS FOR FORMING SPRAY COATING

(57) Abstract:

PROBLEM TO BE SOLVED: To considerably increase the corrosion resistance and durability by depositing, in place of a conventional vinyl chloride lining, a sprayed coating on the inner surface of a metal tube having a diameter of \leq 450 mm used for water supply pipes in general homes and buildings.

SOLUTION: An angle is formed between a torch and a sprayed coating forming surface by bending the torch 2 side of a thermal spraying gun 1. A wear resistant coating layer 36 is formed on the inner surface of a

bent portion of a powder feed pipe 5 in the inside of the thermal spraying gun 1. The torch 2 is cooled with water. The powder feeding apparatus 15 comprises a powder chamber 16, a gear 17, a variable motor 18, a powder charging port 19, a carrier gas inlet 20, a vibrator air inlet 21, a powder discharging port 22, and a powder feeder 23. The film is deposited by using nozzles 4 of the plurality of thermal spraying guns 1 in a manner displaced like comb teeth or by making the thermal spraying guns 1 face each other from openings at both ends in the long metal pipe 5.

COPYRIGHT: (C)2002,JPO

